



**Mallory Sonalert Products, Inc.**

Part #:

**ZT028LAIC3R**

# Sales Outline Drawing

Revision:

**A**

## Specifications:

### INDIVIDUAL CONTROL OF LIGHT AND SOUND

|                       |   |                               |
|-----------------------|---|-------------------------------|
| Function              | LIGHT   | SOUND                         |
| Sound Level Category  | N/A   | Loud                          |
| Mode of Operation     | Continuous  | Slow Pulse @ 1 PPS            |
| Lens Color            | Opaque White  | N/A                           |
| LED Color             | RED   | N/A                           |
| Rated Voltage         | 24 Vac/dc   | 24 Vac/dc                     |
| Voltage Range         | 20 to 28 VAC/DC   | 20 to 28 VAC/DC               |
| Power Connection      | L~ to ~Vac/dc & L~ to ~Vac/dc   | S~ to ~Vac/dc & S~ to ~Vac/dc |
| Current Draw          | 25mA MAX  | 25mA MAX                      |
| Frequency             | N/A   | 3900 ± 500 Hz                 |
| Loudness @ 2 FT       | N/A   | 85 to 95 dB(A) Typ.           |
| Housing Material      | 6/6 Nylon, Color: Black   |                               |
| Front Cap Material    | 6/6 Nylon, Color: Opaque White  |                               |
| Storage Temperature   | -40° to +80° C  |                               |
| Operating Temperature | -30° to +65° C  |                               |
| Panel Mounting        | Recommended hole size is 22.5 mm. Thread front will fit standard 22.5mm hole. |                               |
| Knurled Nut           | Used to attach part to panel. The max recommended torque is 10 in-lbs.        |                               |
| Weight (Typical)      | 28 g  |                               |
| NEMA 3R,4X, & 12      | Approved with use of included gasket.   |                               |
| Options               | Please contact factory.   |                               |

## Dimensions: Inches (mm)

**cUL Recognized**

**ROHS Compliant**

